

Friday 8th October 2021

Supplier: DEGAFLOOR NZ (6 Sheffield Street, Levin, 5510, New Zealand).

Sample Description: DEGADUR® 112

Date Tested: September 2021 (Tested by FORAY Laboratories – NATA Accreditation 1231)

Test Method: ASTM D3960-05 Standard Practice for Determining Volatile Organic Compound (VOC)

Content of Paints and Related Coatings. ASTM D3960 as detailed for paints as well as

South Coast Air Quality Management District (SCAQMD) Rule 1168.

Test Data:

Specification  New Zealand Green Building Council  Green Star – Design & As Built NZ V1.0-13.1.1B  Green Star Interiors V1.0-12.1.1B	DEGADUR® 112
One and two pack performance coatings for floors:	15 grams per Litre as VOC content per
140 grams per liter	material

We hereby certify that Degadur® 112 product is below the VOC Content limits of chosen categories specified by New Zealand Green Building Council, Green Star Design & As Built, and Green Star Interiors

Dr. Vyt Garnys

PhD, BSc(Hons) AIMM, ARACI, ISIAQ

ACA, AIRAH, FMA

Managing Director and Principal Consultant

Dr. Tuan Duong PhD, BE (Chem. Eng.)

Senior Consultant

Travis Hale

BSc (Biotechnology) Senior Consultant



Friday 8<sup>th</sup> October 2021

Supplier: DEGAFLOOR NZ (6 Sheffield Street, Levin, 5510, New Zealand).

Sample Description: DEGADUR® 420

Date Tested: September 2021 (Tested by FORAY Laboratories – NATA Accreditation 1231)

Test Method: ASTM D3960-05 Standard Practice for Determining Volatile Organic Compound (VOC)

Content of Paints and Related Coatings. ASTM D3960 as detailed for paints as well as

South Coast Air Quality Management District (SCAQMD) Rule 1168.

Test Data:

Specification New Zealand Green Building Council Green Star – Design & As Built NZ V1.0-13.1.1B Green Star Interiors V1.0-12.1.1B	DEGADUR® 420
One and two pack performance coatings for floors:	61 grams per Litre as VOC content per
140 grams per liter	material

We hereby certify that Degadur® 420 product is below the VOC Content limits of chosen categories specified by New Zealand Green Building Council, Green Star Design & As Built, and Green Star Interiors

Dr. Vyt Garnys

PhD, BSc(Hons) AIMM, ARACI, ISIAQ

ACA, AIRAH, FMA

Managing Director and Principal Consultant

Dr. Tuan Duong PhD, BE (Chem. Eng.)

Senior Consultant

Travis Hale

BSc (Biotechnology) Senior Consultant



Friday 8th October 2021

Supplier: DEGAFLOOR NZ (6 Sheffield Street, Levin, 5510, New Zealand).

Sample Description: DEGADUR® 526

Date Tested: September 2021 (Tested by FORAY Laboratories – NATA Accreditation 1231)

Test Method: ASTM D3960-05 Standard Practice for Determining Volatile Organic Compound (VOC)

Content of Paints and Related Coatings. ASTM D3960 as detailed for paints as well as

South Coast Air Quality Management District (SCAQMD) Rule 1168.

Test Data:

Specification New Zealand Green Building Council Green Star – Design & As Built NZ V1.0-13.1.1B Green Star Interiors V1.0-12.1.1B	DEGADUR® 526
One and two pack performance coatings for floors:	18 grams per Litre as VOC content per
140 grams per liter	material

We hereby certify that Degadur® 526 product is below the VOC Content limits of chosen categories specified by New Zealand Green Building Council, Green Star Design & As Built, and Green Star Interiors

Dr. Vyt Garnys

PhD, BSc(Hons) AIMM, ARACI, ISIAQ

ACA, AIRAH, FMA

Managing Director and Principal Consultant

Dr. Tuan Duong PhD, BE (Chem. Eng.)

Travis Hale BSc (Biotechnology) Senior Consultant **Senior Consultant** 



Friday 8th October 2021

Supplier: DEGAFLOOR NZ (6 Sheffield Street, Levin, 5510, New Zealand).

Sample Description: DEGADUR® 527

Date Tested: September 2021 (Tested by FORAY Laboratories – NATA Accreditation 1231)

Test Method: ASTM D3960-05 Standard Practice for Determining Volatile Organic Compound (VOC)

Content of Paints and Related Coatings. ASTM D3960 as detailed for paints as well as

South Coast Air Quality Management District (SCAQMD) Rule 1168.

Test Data:

Specification New Zealand Green Building Council Green Star – Design & As Built NZ V1.0-13.1.1B Green Star Interiors V1.0-12.1.1B	DEGADUR® 527
One and two pack performance coatings for floors:	12 grams per Litre as VOC content per
140 grams per liter	material

We hereby certify that Degadur® 527 product is below the VOC Content limits of chosen categories specified by New Zealand Green Building Council, Green Star Design & As Built, and Green Star Interiors

Dr. Vyt Garnys

PhD, BSc(Hons) AIMM, ARACI, ISIAQ

ACA, AIRAH, FMA

Managing Director and Principal Consultant

Dr. Tuan Duong PhD, BE (Chem. Eng.)

Senior Consultant

Travis Hale

BSc (Biotechnology) **Senior Consultant**