



Solid Particleboard Core Interior Door Superior Doors

Final Assembly: Papakura, Auckland, New Zealand

Life Expectancy: 10 Year(s)

End of Life Options: Salvageable/Reusable in its Entirety,
Landfill (100%)

Ingredients:

Particleboard Core: Natural softwoods; Urea, polymer with formaldehyde and 1,3,5-triazine-2,4,6-triamine (primary CASRN is 25036-13-9)¹; Paraffin; **MDF:** Natural softwoods; Urea, polymer with formaldehyde¹; Water; Paraffin; **Finger jointed Pine :** Natural softwoods; Polyvinyl alcohol; Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,3-diisocyanatomethylbenzene, hydrazine and 2-methyloxirane polymer with oxirane ether with 1,2,3-propanetriol (3:1); Polymethylene polyphenyl isocyanate; 4,4'-Methylenediphenyl diisocyanate; Benzene, 1-isocyanato-2-[(4-isocyanatophenyl)methyl]-; Hexane, 1,6-diisocyanato-, homopolymer; Morpholine, 4,4'-(oxydi-2,1-ethanediyl)bis-; **PVA Adhesive:** Polyvinyl alcohol; Undisclosed (0.066-0.079%)²; **Coating:** 2-Propenoic acid, (1-methyl-1,2-ethanediyl) bis[oxy(methyl-2,1-ethanediyl)] ester; Amorphous silica; Titanium dioxide; Undisclosed (0.017-0.122%)²; Undisclosed (0.017-0.122%)²; 2-Propenoic acid, 1,6-hexanediyl ester

¹LBC Temp Exception RL-009 - Formaldehyde

²LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-------------------------------|
| <input type="checkbox"/> LBC Red List Free | % Disclosed: 99.68% at 100ppm |
| <input checked="" type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Low Risk Wood

SPD-0003

EXP. 01 NOV 2025

Original Issue Date: 2024